



PRODUCT: Gemcoat-WB Mold-Resistant Coating Additive™ FORMULA NUMBER: 86T-128

OBJECT FINISHED: Concrete Masonry Units

WEIGHT/GALLON:	8.46 lbs	RECOMMENDED REDUCTION:	1 oz : 1 gal
VISCOSITY:	12-15" Zahn #2	REDUCER:	Gemcoat-WB™
GRIND:	N/A	REDUCED VISCOSITY:	12-15" Zahn #2
WEIGHT SOLIDS:	19.70%	RECOMMENDED FILM THICKNESS:	
V.O.C.:	1.75 lb/gal (minus exempt) 209 g/l (minus exempt) 2.23 lb/gal solids	WET:	N/A
VOLUME SOLIDS:	21.73%	DRY:	N/A
COVERAGE:	N/A	FLASH TIME:	N/A
SUBSTRATE PREP.:	N/A	BAKE TIME:	N/A
APPLICATION METHOD:	N/A	BAKE TEMPERATURE	N/A
EQUIPMENT SETTINGS:	N/A	OVEN TYPE:	N/A
APPLIED OVER:	N/A	GLOSS:	N/A
USED UNDER:	N/A	HARDNESS:	N/A
		IMPACT RESISTANCE:	N/A

REMARKS: This additive was designed for use with our clear Gemcoat-WB™ sealer for concrete masonry units. This additive will create an anti-microbial film that will inhibit the growth of bacteria, mold and mildew on the dried film.

Use 1 oz to every gallon of clear Gemcoat-WB™ sealer.

DATE ISSUED: 06/01/2015 COMPLETED BY: Terry Bartholomew