

SAFETY DATA SHEET

Revision 1
Prepared 2015-05-21

Section 1 – Chemical Product and Company Information

Product Name: GEMCOAT-WB™
Product Code: 96F-163B

Product Uses: Sealing masonry units that have a ground or milled face finish.

Distributor:
York Building Products
950 Smile Way
York, PA 17404

Manufactured by:
Chemcoat, Inc.
P.O. Box 188
2790 Canfield Lane
Montoursville, PA 17754

IN CASE OF EMERGENCY:
Chem-tel
800-255-3924

Section 2 – Hazards Identification

GHS Ratings:

GHS Hazards:

GHS Precautions:

Routes of Entry:

Inhalation; Skin Contact; Eye Contact; Ingestion

Exposure to this material may affect the following organs:

Eyes; Liver

Effects of Overexposure:

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA, or ACGIH.

Section 3 – Composition / Information on Ingredients

Chemical Name / CAS No	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Dipropylene Glycol Butoxy Ether 29911-28-2 2.77 percent Vapor Pressure: .1 mm Hg @ 20 C	Not Listed	Not Listed	
Dipropylene Glycol Monomethyl Ether 34590-94-8 1.38 percent Vapor Pressure: .5 mm Hg @ 68 F	Skin: VPEL 100 ppm – TWA Skin: VPEL 150 ppm - STEL	Skin: VPEL 100 ppm – TWA Skin: VPEL 150 ppm - STEL	

Section 4 – First Aid Measures

Inhalation: Move person to fresh air. If breathing has stopped, administer artificial respiration. Seek medical attention!

Eye Contact: In case of eye contact, flush the eyes with water for fifteen (15) minutes. If contact lenses are worn, quickly remove them, then flush the eyes with water. Have a physician examine the eyes.

Skin Contact: In case of skin contact, remove contaminated clothing. Flush the skin with large amounts of water, then wash the skin with soap and water.

Ingestion: Do not induce vomiting. This may cause chemical pneumonitis and pulmonary edema. If vomiting occurs spontaneously, keep the head below the hips to prevent aspiration of liquid into the lungs. Seek immediate medical attention.

Section 5 – Fire Fighting Methods

Flash Point: > 100°C (>212°F)

Auto-ignition:

LEL: 0.6%

UEL: 20.4%

Extinguishing Media: Use carbon dioxide (CO₂), foam, dry chemical, or water spray/water fog extinguishing system.

Unusual Fire and Explosion Hazards: Vapors may travel considerable distance by air and become ignited by ignition sources.

Hazardous Combustion Products: Oxides of carbon.

Fire Fighting Instructions: Full protective equipment including self-contained breathing apparatus should be used.

Fire Equipment: Water spray may not be effective; use fog nozzles.

Section 6 – Accidental Release Measures

Spill and Leak Procedure: Eliminate all ignition sources. Ventilate the area. Use appropriate respirator and protective clothing.

Small Spills: Contain spill areas with dikes. Recover spilled material into containers. Absorb remainder with absorbent material.

Large Spills: If small spill measures do not contain the spill, notify local authorities and/or the fire department.

Section 7 – Handling and Storage

Handling: Avoid prolonged breathing or contact with product. Keep containers closed when not in use. Do not cut, drill, grind, or weld near containers even when empty. Use non-sparking tools when working around this material.

Storage Requirements: Protect from freezing. Keep containers closed when not in use. Keep away from excessive heat, open flames, or sparks.

Regulatory Requirements: Consult national, state and local environmental laws.

Section 8 – Exposure Controls / Personal Protection

Chemical Name / CAS No	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
29911-28-2	Not Listed	Not Listed	
34590-94-8	Skin: VPEL 100 ppm – TWA Skin: VPEL 150 ppm - STEL	Skin: VPEL 100 ppm – TWA Skin: VPEL 150 ppm - STEL	

Ventilation: Exhaust as required to keep exposure below Threshold Limit Values.

Protective Gear: If ventilation equipment cannot control exposures below the TLV's, wear a properly fitted organic/particulate NIOSH/MSHA-approved respirator. Wear rubber or neoprene protective gloves for repeated or prolonged skin contact. Wear safety glasses or face shield for eye protection.

Section 9 – Physical and Chemical Properties

Appearance	Viscous liquid dispersion
Odor	
Physical State	Liquid
Vapor Density	Heavier than air
Evaporation Rate	Faster than ether
% Volume Volatile	78.29

Formula Lb/Gal	8.49
Vapor Pressure	0.36 mm Hg @ 20C
Boiling Range	100°C
Density	1.01927
Flash Point	>212 F
Lbs VOC/Gallon Solids	1.68
Explosive Limits	1% - 20%

Section 10 – Stability and Reactivity

Stability: Stable.

Incompatibility: Strong acids or bases.

Hazardous Decomposition: Oxides of carbon and nitrogen.

Hazardous polymerization will not occur.

Section 11 – Toxicological Information

Dipropylene Glycol Butoxy Ether

LD 50:

Dipropylene Glycol Monomethyl Ether

Section 12 – Ecological Information

Ecotoxicity: Protect environment from spills and releases.

Section 13 – Disposal Considerations

Disposal: As the US EPA, state, local or other regulatory agency may have jurisdiction over the disposal of your facility's waste, it is incumbent on you to learn and satisfy all the regulations which affect you. Dispose of in accordance to government regulations. Destroy by liquid incineration by certified environmental service group.

Section 14 – Transport Information

Protect from freezing.

Agency
DOT

Proper Shipping Name
Paint

UN Number
Not required

Packing Group

Hazard Class
Not regulated

Section 15 – Regulatory Information

Additional regulatory listings where applicable.

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>




Toxic Substances Control Act (TSCA): All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory.

Section 16 – Other Information

Hazardous Material Information System (HMIS)

National Fire Protection Association (NFPA)

HEALTH	<input type="text" value="2"/>	HMIS & NFPA Hazard Rating Legend * = Chronic Health Hazard 0 = INSIGNIFICANT 1 = SLIGHT 2 = MODERATE 3 = HIGH
FLAMMABILITY	<input type="text" value="1"/>	
PHYSICAL HAZARD	<input type="text" value="0"/>	
PERSONAL PROTECTION	<input type="text"/>	



Date prepared: 5/21/2015

Every effort has been made to ensure that the safety information on this sheet is accurate, but because Chemcoat, Inc. has no control over the condition under which the product will be used, liability is limited exclusively to replacement or refund of the purchased price of this product. Except as stated herein, there are **NO EXPRESS OR IMPLIED WARRANTIES INCLUDING IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE**. Chemcoat, Inc. assumes no liability for injury or incidental or consequential damages arising out of the storage and handling or use of this product.