



PRODUCT: Gemcoat Mold-Resistant Coating Additive™      FORMULA NUMBER: 86T-127

OBJECT FINISHED: Concrete Masonry Units

---

WEIGHT/GALLON:	8.13 lbs	RECOMMENDED REDUCTION:	1 oz : 1 gal
VISCOSITY:	14-16" Zahn #2	REDUCER:	Gemcoat™
GRIND:	7.0 Hegman	REDUCED VISCOSITY:	14-16" Zahn #2
WEIGHT SOLIDS:	23.18%	RECOMMENDED FILM THICKNESS:	
V.O.C.:	2.73 lb/gal (minus exempt) 327 g/l (minus exempt) 4.40 lb/gal solids 67.24% VOC exempt by wt. 9.58 % VOC by wt.	WET:	N/A
VOLUME SOLIDS:	17.70%	DRY:	N/A
COVERAGE:	N/A	FLASH TIME:	N/A
SUBSTRATE PREP.:	N/A	BAKE TIME:	N/A
APPLICATION METHOD:	N/A	BAKE TEMPERATURE	N/A
EQUIPMENT SETTINGS:	N/A	OVEN TYPE:	N/A
APPLIED OVER:	N/A	GLOSS:	N/A
USED UNDER:	N/A	HARDNESS:	N/A
		IMPACT RESISTANCE:	N/A

---

REMARKS: This additive was designed for use with our Gemcoat™ sealer for concrete masonry units. This additive will create an anti-microbial film that will inhibit the growth of bacteria, mold and mildew on the dried film.

Use 1 oz to every gallon of Gemcoat™ sealer.

DATE ISSUED: 06/01/2015

COMPLETED BY: Terry Bartholomew