



Shown: Fieldstone

CornerStone 100®

THOMASVILLE, PA PLANT

Each lightweight CornerStone 100® unit has a large hollow core, unique SecureLug™ connection, unit gravel infill and tapered sides.

These features allow maximum flexibility, ease of installation and cost savings while maintaining high structural integrity of both gravity and geosynthetic reinforced walls. Setback = 5/8"/course (4.5 degrees).

When filled with gravel, this unit's interlock provides high shear resistance, excellent connection strength to geosynthetic reinforcement and maximum layout versatility.

CornerStone 100 units are produced in accordance with ASTM C 1372, and are ICC Evaluation Service Approved.

For more info or technical consultation:

DC, MD, VA, WV:

Doug Statler

dstatler@yorkbuilding.com

240.357.8389

DE, NJ, NY, PA:

Paul Hartline

phartline@yorkbuilding.com

717.286.8169

 **YORK** BUILDING
PRODUCTS
A STEWART COMPANY

5952 Lincoln Hwy West
Thomasville, PA 17364
yorkbuilding.com

CornerStone 100[®]

THOMASVILLE, PA PLANT



CornerStone 100 Unit
(Shown Upside Down)




Solid Corner Unit



4" Rectangle Cap

Product	Setback	Batter	Shapes	H (in)	W (in)	D (in)	Approx Wgt.	SF/Pal	Pc/Pal	Lbs/Pal
Cornerstone 100 (Thomasville Plant)	5/8"	4.5°	CS 100 Unit	8	18	12	81	40	40	3270
			8" Solid Corner Unit	8	18	9	104	30	30	3170
			4" Rectangle Cap	4	18	12	70	72 LF	48	3400

Thomasville Colors



Coastal Tan



Fieldstone



Granite



Mesquite*
(*Premium color)