



PRODUCT DATA SHEET

Product: Gemcoat Zero VOC

Object Finished: Masonry Building Blocks

Formula Number: 96H-177

Product Description

This product was designed for use as a protective and decorative coating for cementitious substrates. This product is a ZERO VOC version of 96G-168A 3.0 Clear Block Coating. This coating is compatible with 96G-168A both in the wet and dry states.

Advantages

- Full gloss
- Good UV resistance
- Good block resistance
- Good chemical resistance
- ZERO VOC

Product Information

Weight per Gallon: 8.77 lbs

Viscosity: 25-35" Zahn #2

Weight Solids: 27.16%

Volume Solids: 26.35%

VOC: 0.00 lbs/gal (0.0 g/L)

Packaging: 5-gallon pail, 50-gallon drum, 265-gallon tote

Appearance: Clear liquid

Storage: Sealed container. Shelf life is 1 year from Date of Manufacture in Original sealed container



PRODUCT DATA SHEET

APPLICATION INFORMATION

For Spray Application: Adjust settings to achieve a smooth continuous film

Film Thickness: 4.0-6.0 mils wet, 1.0-1.5 mils dry

Bake Time and Temperature: Airdry- 15 minutes

Coverage: 423 sq. ft @1 mil

Mixing: No recommended reduction, use as supplied. Acetone or TBAC if needed.

General Use: Substrate prep, surface must be clean and dry of oil and dust. Only apply when surface temperature is between 40°F (4°C) and 95°F (35°C). Allow at least 1 hour after application before frost or freezing temperatures.

BASIS OF PRODUCT DATA

Results may vary depending on equipment, atmospheric conditions, mixing methods, etc.

OTHER RESTRICTIONS

See Legal Disclaimer

ENVIRONMENTAL, HEALTH AND SAFETY

Refer to the Safety Data Sheet

LEGAL DISCLAIMER

- **Keep container tightly closed**
- **Keep out of reach of children**
- **For industrial use only**
- **Not for internal consumption**
- **For professional use only**

Prior to each use of any product the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet; which are available upon request