



PRODUCT: Graffiti-Clean™  
OBJECT FINISHED: Concrete Masonry Units

FORMULA NUMBER: TL-113

---

DENSITY LBS/GAL:	8.78 lbs	RECOMMENDED REDUCTION:	Use as supplied
VISCOSITY:	30" Zahn #3 minimum	REDUCER:	None
GRIND:	N/A	REDUCED VISCOSITY:	Use as supplied
WEIGHT % SOLIDS:	7.13%	RECOMMENDED FILM THICKNESS:	N/A
V.O.C.:	8.15 lbs/gal (978g/l) 92.8% VOC by weight	WET:	N/A
VOLUME % SOLIDS:	3.41%	DRY:	N/A
COVERAGE:	N/A	FLASH TIME:	10 seconds to 20 minutes
SUBSTRATE PREP.:	N/A	BAKE TIME:	N/A
APPLICATION METHOD:	Apply Graffiti Wizard using a brush or cloth	BAKE TEMPERATURE	N/A
EQUIPMENT SETTINGS:	N/A	OVEN TYPE:	N/A
APPLIED OVER:	N/A	GLOSS:	N/A
USED UNDER:	N/A	HARDNESS:	N/A
		IMPACT RESISTANCE:	N/A

---

REMARKS: GRAFFITI WIZARD cleaner removes most paints and permanent markers, varnish, glue, crayon, oil, grease, food spills, etc.

- Shake well before using.
- Apply Graffiti Wizard using a brush or cloth.
- Let stand 10 seconds to 20 minutes, depending on the severity of the stain.
- If using on a more porous or textured surface, a stiff bristle brush may be required.
- Wipe off with a damp cloth.
- After stain is removed, neutralize the surface with water and a clean, damp cloth.
- Make sure all of the Graffiti Wizard is removed from the surface.

DATE ISSUED: 2/28/12

COMPLETED BY: S Sander